

Declaration of Performance

Slide Monorail - 01 No

Slide Mono Sliding Patio Door (Not On Escape Routes)

13

Advanced Aluminium

Issue 1 01/07/2013

Characteristics	Performance		AVCP	hEN
Dangerous substances	As required by regulation		System 3 Notified bodies performed the determination of the	
Thermal transmittance	Uw 2.1 W/m²k (1) Or better than			
	This figure is based upon			
	Centre Pane Ug of	1.2	product-type on the basis of type testing, type calculation, tabulated values or	EN 14351-1:2010
	Spacer	Warm Edge		
	(a higher figure would be achieved with a worse performing unit or edge spacer)		descriptive doccumentation of the product, and issueing of test/calculation reports under system 3	
Load bearing capacity of safety devices	None			
Ability To Release	npd			

Notified Bodies:-

BSI & CWCT (Smart Systems Limited)

The performance of the products certified with the above unique identification codes are in conformity with the relevant declared performances. This declaration of performance is issues under the sole responsibility of Advanced Aluminium, Ayton Road, Wymondham, Norfolk, NR18 OQH.

Signed for and on behalf of the manufacturer by:

Name and Function	Place and date of issue	Signature	
Mitul Patel	Norwich, 1st July 2013	CUHAL	
Business Systems Manager	MOI WICH, 150 July 2015		