



13

Declaration of Performance

No DF75 DCS - 02

Dualframe 75 Casement
(Not On Escape Routes)

Advanced Aluminium

Issue 1 01/07/2013

Characteristics	Performance	AVCP	hEN
Dangerous substances	None	System 3 Notified bodies performed the determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product, and issueing of test/calculation reports under system 3	EN 14351-1:2010
Thermal transmittance	Uw 1.9 W/m ² k (1) Or better than		
	This figure is based upon Centre Pane Ug of 1.2 Spacer Warm Edge (a higher figure would be achieved with a worse performing unit or edge spacer)		
Load bearing capacity of safety devices	350N		
Ability To Release	npd		

Notified Bodies:-

- (1) Exova Warringtonfire EC No. 1104 (Report No WIL328908)
(2) Chiltern Dynamics CN 1762 (Chilt/P08136/tec1)

The performance of the products certified with the above unique identification codes are in conformity with the relevant declared performances. This declaration of performance is issues under the sole responsibility of Advanced Aluminium, Ayton Road, Wymondham, Norfolk, NR18 0QH.

Signed for and on behalf of the manufacturer by:

Name and Function	Place and date of issue	Signature
Mitul Patel Business Systems Manager	Norwich, 1st July 2013	